

Declaration of Performance

No.: 45393613024/ZO-07/24

Product type: **MEDITERANO FLAT**
(production class II)

1. Identification code:		ZO-07			
2. Type, serial number:		21300 21360 42300			
3. Intended use:		Wall cladding			
4. Performance constancy: assessment/check:		System 4			
5. Manufacturer:		PERFORMS:		a) factory production control b) initial type testing	
6. European Technical Assessment		/			
7. Declared performance					
Dimensions:	Length	mm	Various shapes	Various shapes	Various shapes
	Width (thickness)	mm	20 – 45	20 – 45	20 – 45
	Height	mm	various shapes	various shapes	various shapes
	Permitted deviation	class	±8	±8	±8
	Permitted deviation	class		D1	
					STANDARDS
Flatness of bed faces:		mm		NPD	
Parallelism of bed faces:		mm		NPD	
Surface flatness:		mm		NPD	
Net dry density (mean):		kg/m ³		1220	HRN EN 772-13
Compressive strength (mean) σ_{mean} :		N/mm ²		20,8	HRN EN 12390-3
Water absorption:		%		16	
Thermal conductivity:		W/mK		0,358	HRN EN 12664
Water vapour permeability		μ		51	ISO 12572
Reaction to fire:		class		A1	HRN EN 13501-1
Flexural strength:		N/mm ²		3,3	HRN EN 14617-2
Flexural strength (after 25 freeze/thaw cycles):		N/mm ²		3,1	HRN EN 14617-2
Rustik kamen products are handmade; minor variations and irregularities in colour and dimensions are expected and specified as such.					

Authorised representative:
Director

Signed for the manufacturer:
Ivana Boljat Ilečić

Date:
30.12.2024.

(5.) RUSTIK KAMEN d.o.o.
Ulica Ljudevita Posavskog 34
10000 Zagreb

Declaration of Performance

No.:	45393613024/ZO-07/24
Product type:	MEDITERANO CORNER (production class II)

1. Identification code:		ZO-07			
2. Type, serial number:		21300 21360 42300			
3. Intended use:		Wall cladding			
4. Performance constancy: assessment/check:		System 4			
5. Manufacturer:		PERFORMS:		a) factory production control b) initial type testing	
6. European Technical Assessment		/			
7. Declared performance					
Dimensions:	Length	mm	Various shapes	Various shapes	Various shapes
	Width (thickness)	mm	20 – 50	20 – 50	20 – 50
	Height	mm	various shapes	various shapes	various shapes
	Permitted deviation	class	±8	±8	±8
	Permitted deviation	class		D1	
					STANDARDS
Flatness of bed faces:		mm		NPD	
Parallelism of bed faces:		mm		NPD	
Surface flatness:		mm		NPD	
Net dry density (mean):		kg/m ³		1220	HRN EN 772-13
Compressive strength (mean) σ _{mean} :		N/mm ²		20,8	HRN EN 12390-3
Water absorption:		%		16	
Thermal conductivity:		W/mK		0,358	HRN EN 12664
Water vapour permeability		μ		51	ISO 12572
Reaction to fire:		class		A1	HRN EN 13501-1
Flexural strength:		N/mm ²		3,3	HRN EN 14617-2
Flexural strength (after 25 freeze/thaw cycles):		N/mm ²		3,1	HRN EN 14617-2
Rustik kamen products are handmade; minor variations and irregularities in colour and dimensions are expected and specified as such.					

Authorised representative:
Director

Signed for the manufacturer:
Ivana Boljat Ilečić

Date:
30.12.2024.

(5.) RUSTIK KAMEN d.o.o.
Ulica Ljudevita Posavskog 34
10000 Zagreb

Rustik kamen d.o.o.

Sjedište: Ulica Ljudevita Posavskog 34, HR - 10 000 Zagreb / Ured i proizvodnja: Oreškovićeve 1a, HR - 10 010 Zagreb
OIB: 45393613024, tel: +385 (0)1 345 00 54, fax: +385 (0)1 345 00 95, e-mail: info@rustik-kamen.hr, www.rustik-kamen.hr