TECHNICAL DATA SHEET

STAIR TREAD

BUSH-HAMMERED

RUSTIKKAMEN

10000



21000



MODEL		
THICKNESS	3,0 cm	4,0 - 4,5 cm
DIMENSIONS	35 x 35 cm	35 x 35 cm
WEIGHT	12,00 kg/pcs	16,00 kg/pcs
PACKAGING	pallet	pallet
EURO PALLET	80 pcs	60 pcs
PALLET WEIGHT	960,00 kg	950,00 kg
ADHESIVE CONSUMPTION	7 - 8 kg/m^2	10 kg/m^2
GROUT CONSUMPTION	7 kg/m^2	9 kg/m^2

MODEL DESCRIPTION: Bush-hammered stair treads have a rougher, grooved texture that gives surfaces a striking appearance. Available in several durable natural colours suited to all outdoor conditions. They enhance the appearance and functionality of floor surfaces while adding structural stability and strength.

APPLICATIONS:

For private and public use as pool coping.

SAFETY:

The slabs are slip resistant to HRN EN 1339.

CARE AND MAINTENANCE:

Dry and wet cleaning. Use soft brushes, not wire brushes.

PROPERTIES:

› Resistance to frost and de-icing salt
› Abrasion and slip resistance
› Profiled, uneven surfaces
› Profiled, uneven edges

BUILDING AND PHYSICAL INFORMATION:

In addition to slip resistance, the product has satisfactory frost and abrasion resistance, strength and dimensions, all to HRN EN 1339.

Rustik kamen d.o.o.
Registered office: Ulica Ljudevita Posavskog 34, HR - 10 000 Zagreb / Office and production: Oreškovićeva 1a, HR - 10 010 Zagreb
OIB: 45393613024, tel: +385 (0)1 345 00 54, fax: +385 (0)1 345 00 95, e-mail: info@rustik-kamen.hr, www.rustik-kamen.hr

BUSH-HAMMERED

RUSTIKKAMEN

COLOUR AND SURFACE:

Variations in slab colour and surface result from natural materials (cement, sand, etc.) and cannot be avoided in production. Coloured slabs contain iron oxide pigments resistant to weather and UV exposure, which may show slight shade differences. Weathering may also slightly change colour and texture, giving slabs a natural appearance and patina. Differences are particularly noticeable where identical slabs are sheltered (from rain, sun and ice) or exposed directly to the weather. For a natural appearance, take slabs alternately from several open pallets during installation. For these reasons, differences in colour or texture do not impair quality and do not constitute grounds for a claim.

FROST AND DE-ICING SALT RESISTANCE:

Rustik kamen tests all products for frost and salt resistance to HRN EN 1338:2004, HRN EN 1339:2004 and HRN EN 1340:2004. Use de-icing agents suitable for concrete products (NaCl-based). Other sulphate-based agents may damage concrete slab surfaces.

EFFLORESCENCE:

White marks may sometimes appear on slab surfaces. This natural occurrence in concrete is known as efflorescence. Moisture from rain or condensation enters the product and partly dissolves the lime. The solution reaches the surface; as water evaporates, lime remains as white marks that temporarily resist washing. These marks cannot be prevented during production. Their intensity depends on weather conditions (frost, rain, snow, wind...). Weathering gradually washes away the surface lime more readily until it eventually disappears. The marks can also be removed with specialist cleaning products. Efflorescence does not affect the quality of Rustik kamen products and therefore does not constitute grounds for a claim.

COLOUR VARIATIONS:

Weather and external influences may occasionally cause slight yellow or brown surface discolouration. As we cannot control its occurrence, such discolouration does not constitute grounds for a claim.

CRACKS:

Cracks may occasionally appear on the product surface, visible only when wet and not when dry. Surface cracks do not reduce the product's usability.

CLAIMS:

Buyers must visually check product quality and quantity on receipt and before installation. Claims concerning installed products and additional flooring installation costs cannot be accepted.

ORDER QUANTITIES:

When ordering and buying our products, we recommend buying extra pieces to replace slabs if they suffer mechanical damage or similar.

**The Rustik kamen technical manual is available when purchasing Rustik kamen products or at www.rustik-kamen.hr*