RUSTIKKAMEN

RUSTIK SEAL

LIQUID BREATHABLE COATING **FOR PROTECTION AND IMPREGNATION** OF CONCRETE, NATURAL AND DECORATIVE STONE

Protects porous surfaces deeply from water, oil and stains; easier cleaning. No film; colourless when dry, non-yellowing, enhances the natural substrate tone.



PACKAGING: 1L / 5L

DESCRIPTION:

RUSTIK SEAL provides deep protection and a protective barrier for porous surfaces such as concrete, natural and decorative stone. It creates a water- and oil-repellent, breathable surface that resists stains and is easy to clean. Colourless when dry, it enhances colour intensity without yellowing. The product is an aqueous emulsion without organic solvents, based on silanes, siloxanes and C6 fluorides. Final properties are achieved 3-4 days after application.

BENEFITS:

› Prevents ingress of water- and oil-based liquids
› Limits efflorescence
› Limits mould growth
› Makes treated surfaces easier to clean
› Breathable; no film formation
› Invisible when dry
› UV resistant (non-yellowing)
› Easy application to vertical and horizontal, indoor and outdoor surfaces
› Harmless and non-toxic

APPLICATION INSTRUCTIONS:

The surface must be dry, sound, clean and free of stains and dust. Shake the container well before use. Do not dilute RUSTIK SEAL. Apply with a brush, roller or low-pressure pump until the surface is saturated. On vertical surfaces, apply from bottom to top. Drying time is 24 hours (without rain); full protection is achieved after 3 to 4 days. Do not apply at high temperatures or in strong sunlight. Use in adequately ventilated areas. No protective clothing for skin or hands is required. Wear safety goggles if splashing is possible.

Rustik kamen d.o.o.
Registered office: Ulica Ljudevita Posavskog 34, HR - 10 000 Zagreb / Office and production: Oreškovićeva 1a, HR - 10 010 Zagreb
OIB: 45393613024, tel: +385 (0)1 345 00 54, fax: +385 (0)1 345 00 95, e-mail: info@rustik-kamen.hr, www.rustik-kamen.hr

RUSTIK SEAL

RUSTIKKAMEN

PROPERTIES:

CHARACTERISTIC	PROPERTY
PHYSICAL STATE AT 20°C	liquid
COLOUR	milky yellow-white
ODOUR	odourless
DENSITY	1,0 kg/l
SOLUBILITY IN WATER	fully soluble
CONSUMPTION	150 — 250 ml/m^2 (depending on substrate absorbency)

SHELF LIFE AND STORAGE:

Store in a dark, dry place, never below 5°C or above 35 °C. Properly stored in its original packaging, the product retains its properties for 12 months from manufacture.

WARNINGS:

Clean tools with clean water immediately after use. The properties stated in this data sheet are based on laboratory tests. Information and recommendations for RUSTIK SEAL application reflect our current experience and knowledge, provided the product is correctly stored and used as instructed.

NOTE:

Re-treat surfaces every two years, depending on the frequency of surface wear.

Rustik kamen d.o.o.
Registered office: Ulica Ljudevita Posavskog 34, HR - 10 000 Zagreb / Office and production: Oreškovićeva 1a, HR - 10 010 Zagreb
OIB: 45393613024, tel: +385 (0)1 345 00 54, fax: +385 (0)1 345 00 95, e-mail: info@rustik-kamen.hr, www.rustik-kamen.hr